





Office: 1 (778) 785-0255 Text: 1 (236) 515-1580 www.prosolver.ca/abouthanit



OUTDOOR SURFACES

For the love of dry feet!

When grass, rain and people come together, you're going to get mud. For cases like these, we recommend our ground cover. Whether it's for campsites, riding arenas, parking lots, exhibition sites, beer tents or construction sites, we have the right solution for you. Our footpath planks, boards, paddock slabs, hexagonal eco slabs and Hanpave™ will keep you on solid ground. All our products are robust and lightweight.

We make our decking and paving from heavy-duty hanit. It's suitable for practically any purpose and can be laid quickly thanks to our effective linking system. Even large areas can be covered quickly and if used for temporary purposes, it can be removed just as easily.

- » Strong enough for heavy-duty use
- » Quick and easy to install
- » Can be used as temporary or permanent installations
- » Lightweight
- » Low transport costs due to high loading capacity








FOOTPATH PLANK

Tongue and groove

Colors









15⁄8" x	6¾", reinf	forced				00
Length	Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	ncs.		OLD		NEW
3' 33%"	16.3		Gray	RGA 040 100	\rightarrow	4 100 298
3 378	10.5	75	B row n	RBA 040 100	\rightarrow	4 100 305
4' 11"	24.7	75	Gray	RGA 040 150	→	4 100 299
			B row n	RBA 040 150	\rightarrow	4 100 304
6' 7"	32.8	75	Gray	RGA 040 200	→	4 100 300
			B row n	RBA 040 200	\rightarrow	4 100 303
8' 2"	41.0	75	Gray	RGA 040 250	→	4 100 301
			B row n	RBA 040 250	\rightarrow	4 100 302
9' 10"	49.4	65	Gray	RGA 040 300	→	4 100 153
			B row n	RBA 040 300	\rightarrow	4 100 154

APPLICABLE FOR hanit FOOTPATH **PL ANKS**

Surface:

Grooved profile slip rating R1

BGF-Testing in accordance with ZH1/571 and DIN 51130 Note expansion/contraction due to temperature fluctuations (up to +/- 1.5%) during installation. The material is recycled plastic. Variation in the surface quality is not always be avoidable.



OVERVIEW OF SPANS

Floor surface			
ootpath plank (inch)	Material	Uniformly distributed load: 62.6 psf Point load: 337 lbs	Uniformly distributed load: 104.4 psf Point load: 450 lbs
15/8" x 6¾"	hanit	*235/8"	235/8"
15/8" x 6¾" reinforced	hanit	*3' 33/8"	*3' 33/8"
15/8" x 7¾"	hanit	20¾"	181/8"
15/8" x 7¾" reinforced	hanit	*2' 7½"	2' 7½"
17/8" x 6½"	hanit	*235/8"	22"
17/8" x 6½" reinforced	hanit	*2' 7½"	2' 7½"
23/8" x 7¾"	hanit	*2' 7½"	2' 7½"
23/8" x 7¾" reinforced	hanit	*3' 33/8"	3' 33/8"

Two footpath planks each measuring 15/8" x 6¾" with tongue and groove were tested in combination | * Maximum span due to the creep properties








FOOTPATH PLANK

Colors









15/8" x	7%", rein	forced				\circ
Length	Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	ncs.		OLD		NEW
3' 33/8"	18.5		Gray	RGA 050 100	\rightarrow	4 100 248
3 370	10.5	120	B row n	RBA 050 100	\rightarrow	4 100 253
4' 11"	27.8	60	Gray	RGA 050 150	→	4 100 249
			B row n	RBA 050 150	\rightarrow	4 100 254
6' 7"	37.3	60	Gray	RGA 050 200	→	4 100 250
			B row n	RBA 050 200	\rightarrow	4 100 255
8' 2"	46.3	60	Gray	RGA 050 250	→	4 100 251
			B row n	RBA 050 250	\rightarrow	4 100 256
9' 10"	55.6	56	Gray	RGA 050 300	→	4 100 252
			B row n	RBA 050 300	\rightarrow	4 100 257

NOTE

- » HAHN boards, square profiles, posts and beams will never rot and can be used with virtually any substructure design. Take a look at chapter 1 'Building and Construction' or contact us for expert advice.
- Please refer to the installation recommendations, data sheet, and assembly instructions. These can be found on our website www.hanit.ca and downloaded from the selected product page.









1%" x	6½"					00
Length ft/in	Weight lbs	Qty/Pal pcs.	Color	Item No OLD		Item No
3' 3%"	16.1	75	Gray B row n	RGU 048 100 RBU 048 100	→	4 100 213 4 100 217
4' 11"	24.3	75	Gray B row n	RGU 048 150 RBU 048 150	→	4 100 214 4 100 218
6' 7"	32.4	75	Gray B row n	RGU 048 200 RBU 048 200	→ →	4 100 215 4 100 219
8' 2"	40.6	75	Gray B row n	RGU 048 250 RBU 048 250	→ →	4 100 216 4 100 220
9' 10"	48.5	65	Gray B row n	RGU 048 300 RBU 048 300	→ →	4 100 143 4 100 142

6½", reinf	orced				00
Weight	Qty/Pal	Color	Item No		Item No
lbs	pcs.		OLD		NEW
18 7		Gray	RGA 048 100	\rightarrow	4 100 221
10.7	75	B row n	RBA 048 100	\rightarrow	4 100 225
28.2	75	Gray	RGA 048 150	→	4 100 222
		B row n	RBA 048 150	\rightarrow	4 100 226
37.5	75	Gray	RGA 048 200	→	4 100 223
		B row n	RBA 048 200	\rightarrow	4 100 227
47.0	65	Gray	RGA 048 250	→	4 100 224
		B row n	RBA 048 250	\rightarrow	4 100 228
56.2	55	Gray	RGA 048 300	→	4 100 151
		B row n	RBA 048 300	\rightarrow	4 100 152
	Weight lbs 18.7 28.2 37.5 47.0	18.7 75 28.2 75 37.5 75 47.0 65	Weight lbs Qty/Pal pcs. Color pcs. 18.7 75 Gray B row n 28.2 75 Gray B row n 37.5 75 Gray B row n 47.0 65 Gray B row n 56.2 55 Gray	Weight lbs Qty/Pal pcs. Color oLD 18.7 75 Gray B row n RGA 048 100 28.2 75 Gray RGA 048 150 RBA 048 150 37.5 75 Gray RGA 048 200 RBA 048 200 8 row n RBA 048 200 RBA 048 200 47.0 65 Gray RGA 048 250 8 row n RBA 048 250 56.2 55 Gray RGA 048 300	Weight lbs Qty/Pal color oLD Item No OLD 18.7 75 Gray B row n RGA 048 100 → RBA 048 100 → RBA 048 100 → RBA 048 150 → RBA 048 150 → RBA 048 150 → RBA 048 150 → RBA 048 200 → RBA 048 200 → RBA 048 200 → RBA 048 200 → RBA 048 250 → RBA 0



OPTIONAL: RETROFITTED REINFORCEMENT

- » Flat steel: 15/64" x 1", galvanized
- » Centered on the underside. Ends approx. 2¾" before end of profile
- » Flat steel fixed with clips
- » Double reinforcement available on request
- » For footpath planks 23/8" x 7¾" stronger reinforcement for increased spans available on request





04



23/8" x	7¾"					00	
Length	Weight	Qty/Pal	Color	Item No		Item No	
ft/in	lbs	pcs.		OLD		NEW	
3' 33/8"	24.3	00	Gray	RGU 060 100	\rightarrow	4 100 258	
3 376	21.5	80	B row n	RBU 060 100	\rightarrow	4 100 261	
4' 11"	36.4	40	Gray	RGU 060 150	→	4 100 259	
				B row n	RBU 060 150	\rightarrow	4 100 262
6' 7"	48.5	40	Gray	RGU 060 200	→	4 100 235	
			B row n	RBU 060 200	\rightarrow	4 100 263	
8' 2"	60.6	40	Gray	RGU 060 250	→	4 100 260	
			B row n	RBU 060 250	\rightarrow	4 100 264	
9' 10"	72.8	40	Gray	RGU 060 300	→	4 100 234	
			B row n	RBU 060 300	\rightarrow	4 100 265	

23/8" x	7¾", reinf	orced				00
Length	Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	DCS.		OLD		NEW
3' 33/8"	26.7		Gray	RGA 060 100	\rightarrow	4 100 266
3 370	2017	80	B row n	RBA 060 100	\rightarrow	4 100 271
4' 11"	39.9	40	Gray	RGA 060 150	→	4 100 267
			B row n	RBA 060 150	\rightarrow	4 100 272
6' 7"	53.4	40	Gray	RGA 060 200	→	4 100 268
			B row n	RBA 060 200	\rightarrow	4 100 273
8' 2"	66.6	40	Gray	RGA 060 250	→	4 100 269
			B row n	RBA 060 250	\rightarrow	4 100 274
9' 10"	79.8	40	Gray	RGA 060 300	→	4 100 270
			B row n	RBA 060 300	\rightarrow	4 100 275

TIPS & TRICKS

- » For seasonal installation: Made to measure (length, width, height) pre-assembled boardwalk elements guarantee quick installation in spring and if required, swift storage in the winter months.
- » Ready-assembled footpath sections consist of boards pre-installed on to beams.
- » The beams are positioned so that each section pushes together easily.
- » It's even quicker and easier when using our ready made boardwalk elements in standard dimensions (more on page 73).









hanit ULTRA **FOOTPATH PLANK**

The permanent solution

Colors





1½" x	6"					00
	n Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	pcs.		OLD		NEW
12'	43.0	60	B row n	INT 027 MBR	\rightarrow	4 100 432
			Black	INT 027 BLK	\rightarrow	4 100 431

APPLICABLE FOR ALL hanit ULTRA **PRODUCTS**

» Specially formulated for a smoother look and wider spans











hanit ULTRA DECKING

With a wood-like grain

Colors





11/8"	х 6"					00
Length	n Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	pcs.		OLD		NEW
12'	28.7	60	B row n	INT 037 MBR	→	4 4 100 429
			Black	INT 037 BLK	\rightarrow	4 4 100 430





06



DECKING

Firm footing, every time

Colors





1½" x	¢7¼"					00
Length	Weight	Qty/Pal	Color	Item No		Item No
ft/in	lbs	pcs.		OLD		NEW
6' 7"	22.5	60	B row n Black	TB 2820 200 TS 2820 200	→	4 100 167 4 100 171
9' 10"	33.7	60	B row n Black	TB 2820 300 TS 2820 300	→ →	4 10 0 116 4 100 238





NOTE

- » HAHN boards, square profiles, posts and beams will never rot and can be used with virtually any substructure design. Take a look at chapter 1 'Building and Construction' or contact us for expert advice.
- » Please refer to the installation recommendations, data sheet, and assembly instructions. These can be found on our website www.hanit.ca and downloaded from the selected product page.













PILE

Solid, stable support

Colors





Ø 7¾"						00
Length ft/in	Weight lbs	Qty/Pal pcs.	Color	Item No OLD		Item No NEW
6' 7"	124.6	16	Gray B row n	SG 200 200 SB 200 200	→	3 0 0 0 217 3 000 208
8' 2"	156.5	16	Gray B row n	SG 200 250 SB 200 250	→	3 0 0 0 242 3 0 0 0 241
9' 10"	187.4	16	Gray B row n	SG 200 300 SB 200 300	→	3 0 0 0 2 18 3 0 0 0 2 24
11' 6"	218.5	8	Gray B row n	SG 200 350 SB 200 350	→	3 0 0 0 2 21 3 000 220
13' 1"	249.8	8	Gray B row n	SG 200 400 SB 200 400	→	3000219 3000225
14' 9"	281.1	8	Gray B row n	SG 200 450 SB 200 450	→	3 0 0 0 215 3 000 226
16'	312.2	8	Gray B row n	SG 200 500 SB 200 500	→	3 0 0 0 210 3 000 227
18'	343.5	8	Gray B row n	SG 200 550 SB 200 550	→	3 000 222 3 000 228
19' 8"	347.8	8	Gray B row n	SG 200 600 SB 200 600	→	3 0 0 0 2 2 3



NOTE

Piles with a diameter of 97/8" and a length of up to 19' 8" are available on request.











PRE-ASSEMBLED BOARDWALK ELEMENT


Click, click – done!

Colors















WARRANTY FOR hanit RECYCLED PLASTIC PRODUCTS

1. WARRANTY AND DURATION Subject to any

additional terms, conditions or exclusions contained in the applicable version of HAHN Plastics (North America) Ltd.'s General Terms and Conditions of Business ("GT&Cs"), HAHN Plastics (North America) Ltd.'s ("HAHN") warrants that on delivery, and for a period of 20 years from the date of delivery of the product (the "Warranty Period"), the hanit recycled plastic products shall be delivered free of material defects in design, material and workmanship.

The color of any hanit recycled plastic products and any changes thereto over time is not a part of this warranty. HAHN expressly disclaims any warranty or liability in respect of variations or changes of color to any hanit recycled plastic products delivered to the customer.

2. MATERIAL PROPERTIES OF hanit RECYCLED PLASTIC PRODUCTS

hanit recycled plastic products may show variations in color and dimensions (with a fluctuation of up to +/- 1.5%). hanit recycled plastic products may vary in surface finish and show production-related textured surfaces, inclusions, and cavities. Due to this, the given weight, dimensions, color and surface finish are approximate only and do not form part of this warranty. For further details, see the applicable version of the GT&Cs.

3. WARRANTY CONDITIONS

Subject always to any further conditions contained in the applicable version of GT&Cs and any exclusions, HAHN shall at its option replace and/or repair and/or refund hanit recycled plastic products after a thorough inspection should our goods be found to be defective during the Warranty Period in spite of proper installation,

application and use. Installation and application of

hanit recycled

plastic products according to assembly and installation instructions are a prerequisite for warranty adjustments.

Amsts, reimbursements of transport installation, re-installation, consequential damage, disassembly, or other costs are excluded from this warranty and the customer shall be soley responsible for the costs of same.

4. WARRANTY HANDLING

For correct and speedy processing in case of a warranty claim, please contact HAHN in writing during the Warranty Period and include the following documentation:

- » a copy of the invoice
- » a detailed description of the defect
- » photos and/or a sample of the faulty hanit recycled plastic products

For more information on how a warranty claim will be processed, see the applicable version of the GT&Cs

5. EXCLUSION OF WARRANTY In addition to any

exclusions or restrictions which are set out in the applicable version of the GT&C's, the following items do not constitute warranty

- a) defects that can be ascribed to normal wear and tear
- b) defects such as discoloration and expansion caused by weather and climatic conditions
- c) defects caused by actions of the customer

or third parties (improper use and assembly, modification of the product, use of parts from other suppliers, inappropriate transport, packaging, and storage)

d) dawhagher and/or destruction intentional or unintentional) caused by the actions of the customer or third parties

6. PRODUCTS NOT BENEFITTING FROM 20 YEAR WARRANTY

In addition to any other excluded hanit recycled plastic products set out in the applicable version of the GT&C's, the following hanit recycled plastic products do not benefit from the 20 year warranty set out herein:

a) second quality and remaining stock sales (warranty for these hanit recycled plastic products is restricted to 12 months from the date of delivery)

b) custom-made hanit recycled plastic products, industrial profiles, finished parts and systems (warranty for these hanit recycled plastic products is restricted to 12 months from the date of delivery)

- c) goods not manufactured by companies of the HAHN Group
- d) reinforced posts, warranty for this product is restricted to 5 years from the date of delivery

7. PLACE OF JURISDICTION

The place of jurisdiction and governing law of this warranty shall be as set out in the applicable version of the GT&Cs





Office: 1 (778) 785-0255 Text: 1 (236) 515-1580 www.prosolver.ca/abouthanit